

ARTICULATED TRACTOR

ENGINE

Make
Type
Number of cylinders
Maximum power
Air filter
Cooling system

TRANSMISSION

Clutch
Gear box
Number of wheels
Differential lock

Services brakes
Parking brakes

POWER TAKE OFF

Number of pto axes
Speeds: Independent
Synchronized
Homologated power

STEERING

Mechanical (Standard)
Hydraulic (Optional)

HYDRAULIC SYSTEM

Draw coupling
Electrical equipment

INSTRUMENTS

WHEELS

Front and rear: Standard
Optional

DIMENSIONS AND WEIGHTS

Total length
Wheel base
Total width
Truck width adjustable
Height to steering wheel
Ground height
Weight
Turning angle
Joint angle

CAPACITIES

Engine crankcase
Fuel tank
Transmission case
Rear case

OPTIONS

EBRO 2200

LOMBARDINI LDA 820.
4 Stroke diesel direct injection.
1.817 cm³
21 CV at 3.000 r.p.m.
in oil bath.
Through compelled air.

Dry monodisc 7 1/2"
6 forward speeds, 2 backward speeds.
Four.
Front axle manually operated, rear axle operated with the pedal.
Drums acting on rear axle.
Drums acting on front axle.

2 with reverse turning.
545/760 r.p.m. at 3.000 r.p.m.
According to the advance.
17 CV.

Of circulating bearings.

Independent pump.
Triple coupling, Cath 1 trailer coupling.
Alternator 12 V.
Battery 75 Ah working light and trailer attach.

Gauge meters:
Of oil pressure, handling meters, ammeter, warning.

7.50 x 16
7.50 x 18

2.726 mm
1.150 mm
982 mm
672/778 mm
1.040 mm
230 mm
780 Kg
35°
15°

2,6 l.
7,8 l.
13,0 l.
14,0 l.

Wheels counter, weights, milling coupling
External service, hydraulic take off, wheels spacers.

EBRO 2300

EBRO LOMBARDINI 672.
4 Stroke diesel direct injection.
2.1346 cm³
30 CV at 3.000 r.p.m.
in oil bath.
Through compelled air.

Dry monodisc 8 1/2"
6 forward speeds, 2 backward speeds.
Four.
Front axle manually operated, rear axle operated with the pedal.
Disc in oil bath, hydraulically operated on both axes.
Disc in oil bath, hydraulically operated on both axes.

2 with reverse turning.
545/760 r.p.m. at 3.000 r.p.m.
According to the advance.
26 CV.

Of circulating bearings.
Totally assisted.

Independent pump.
Triple coupling, Cath 1. Trailer coupling.
Alternator 12 V.
Battery 75 Ah, working light and trailer.

Gauge meters: Of oil pressure, handling meters,
ammeter, warning, tractorometer with hourmeter.

7.50 x 16
7.50 x 18

2.768 mm
1.150 mm
1.200 mm
676/994 mm
1.040 mm
230 mm
914 Kg
35°
15°

4,5 l.
16,0 l.
15,0 l.
17,0 l.

Wheels counter, weights, milling coupling
External services hydraulic take off.

2400

LOMBARDINI 832.
2/1.648 cm³
36 CV at 3.000 r.p.m.
in oil bath.
Through compelled air.

Dry monodisc 8 1/2"
6 forward speeds, 2 backward speeds.
Four.
Front axle manually operated, rear axle operated with the pedal.
Disc in oil bath, hydraulically operated on both axes.
Discs in oil bath, hydraulically operated on both axes.

2 with reverse turning.
545/760 r.p.m. at 3.000 r.p.m.
According to the advance.
36 CV.

Of circulating bearings.
Totally assisted.

Independent pump.
Triple coupling, Cath 1 trailer coupling.
Alternator 12 V.
Battery 75 Ah, working light and trailer.

Gauge meters: Of oil pressure, handling meters,
ammeter, warning, tractorometer with hourmeter.

7.50 x 18
11.50 x 18

2.768 mm
1.150 mm
1.200 mm
676/994 mm
1.070 mm
280 mm
930 Kg
35°
15°

3,5 l.
16,0 l.
15,0 l.
17,0 l.

Wheels counter, weights, milling coupling
External service, hydraulic take off.

EBRO

MOTOR IBERICA, S.A.

1.^{er}
PREMIO A LA
SEGURIDAD
FIMA 82

pegasoes

EBRO

2200

2300

2400

